

R5-E.1512-925

| CFM | Static Pressure in Inches W.G. | | | | | | | | |
|-------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.250 | 0.500 | 0.750 | 1.000 | 1.250 | 1.500 | 1.750 | 2.000 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 10000 | 207 / 0.88 | 281 / 1.36 | 350 / 1.96 | 408 / 2.57 | 455 / 3.14 | 498 / 3.69 | 538 / 4.26 | | |
| 12000 | 248 / 1.52 | 312 / 2.11 | 370 / 2.73 | 427 / 3.47 | 475 / 4.21 | 517 / 4.90 | 555 / 5.58 | 591 / 6.25 | 624 / 6.92 |
| 14000 | 289 / 2.40 | 347 / 3.13 | 396 / 3.77 | 446 / 4.57 | 494 / 5.44 | 537 / 6.30 | 575 / 7.14 | 610 / 7.94 | 643 / 8.73 |
| 16000 | 330 / 3.59 | 384 / 4.47 | 426 / 5.15 | 469 / 5.96 | 513 / 6.89 | 555 / 7.89 | 594 / 8.89 | 630 / 9.86 | 662 / 10.81 |
| 18000 | 371 / 5.10 | 422 / 6.17 | 459 / 6.91 | 497 / 7.74 | 536 / 8.69 | 575 / 9.75 | 613 / 10.86 | 649 / 11.99 | 682 / 13.11 |
| 20000 | 412 / 7.00 | 461 / 8.26 | 494 / 9.10 | 528 / 9.95 | 562 / 10.91 | 597 / 11.99 | 633 / 13.16 | 667 / 14.39 | 700 / 15.65 |
| 22000 | 453 / 9.31 | 500 / 10.79 | 531 / 11.73 | 561 / 12.64 | 592 / 13.62 | 623 / 14.70 | 656 / 15.89 | 688 / 17.17 | 720 / 18.52 |

Max Sizeable RPM = 900 RPM. Table shown extended beyond this point for reference only.