

R5-E.4155-925

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
10000	207 / 0.88	281 / 1.36	350 / 1.96	408 / 2.57	455 / 3.14	498 / 3.69	538 / 4.26		
12000	248 / 1.52	312 / 2.11	370 / 2.73	427 / 3.47	475 / 4.21	517 / 4.90	555 / 5.58	591 / 6.25	624 / 6.92
14000	289 / 2.40	347 / 3.13	396 / 3.77	446 / 4.57	494 / 5.44	537 / 6.30	575 / 7.14	610 / 7.94	643 / 8.73
16000	330 / 3.59	384 / 4.47	426 / 5.15	469 / 5.96	513 / 6.89	555 / 7.89	594 / 8.89	630 / 9.86	662 / 10.81
18000	371 / 5.10	422 / 6.17	459 / 6.91	497 / 7.74	536 / 8.69	575 / 9.75	613 / 10.86	649 / 11.99	682 / 13.11
20000	412 / 7.00	461 / 8.26	494 / 9.10	528 / 9.95	562 / 10.91	597 / 11.99	633 / 13.16	667 / 14.39	700 / 15.65
22000	453 / 9.31	500 / 10.79	531 / 11.73	561 / 12.64	592 / 13.62	623 / 14.70	656 / 15.89	688 / 17.17	720 / 18.52

Max Sizeable RPM = 900 RPM. Table shown extended beyond this point for reference only.