

## R-AWPD-30-A

CFM	Static Pressure in Inches W.G.					
	0.000	0.250	0.500	0.750	1.000	1.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000		619 / 0.21	829 / 0.53	989 / 0.93	1123 / 1.39	1241 / 1.91
4000	373 / 0.04	715 / 0.33	936 / 0.73	1102 / 1.20	1239 / 1.72	
6000	558 / 0.13	810 / 0.47	1027 / 0.96	1198 / 1.53		
8000	744 / 0.30	933 / 0.69	1120 / 1.24	1287 / 1.89		
10000	929 / 0.59	1080 / 1.04	1234 / 1.63			
12000	1115 / 1.01	1239 / 1.53				

**Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.**

Motor DHP00265 has an rpm range of 300 to 1150.

Motor DHP1/565 has an rpm range of 300 to 1150.

Motor DTP0026 has an rpm range of 300 to 1150.

Motor DTP0026-50 has an rpm range of 300 to 958.

Motor DTP1/56 has an rpm range of 300 to 1150.

Motor DTP1/56-50 has an rpm range of 300 to 958.

Motor EP00265 has an rpm range of 300 to 1150.

Motor EP1/565 has an rpm range of 300 to 1150.

Motor GP0026 has an rpm range of 300 to 1150.

Motor GP0026-50 has an rpm range of 300 to 958.

Motor GP1/56 has an rpm range of 300 to 1150.

Motor GP1/56-50 has an rpm range of 300 to 958.