

R-AWPD-36-S

CFM	Static Pressure in Inches W.G.							
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3500		366 / 0.17	465 / 0.37	539 / 0.60	600 / 0.85	652 / 1.13	700 / 1.44	743 / 1.75
5500	317 / 0.07	438 / 0.26	536 / 0.51	614 / 0.80	678 / 1.11	734 / 1.44	784 / 1.79	829 / 2.16
7500	432 / 0.19	523 / 0.42	608 / 0.71	683 / 1.05	749 / 1.41	806 / 1.80	858 / 2.20	
9500	546 / 0.38	619 / 0.66	690 / 0.99	757 / 1.37	819 / 1.78	876 / 2.21		
11500	661 / 0.68	722 / 1.00	781 / 1.37	840 / 1.78	895 / 2.23			
13500	776 / 1.09	828 / 1.46	879 / 1.88					
15500	891 / 1.66							

Max Sizeable RPM = 900 RPM. Table shown extended beyond this point for reference only.

Motor DHP00365 has an rpm range of 300 to 900.

Motor DHP00545 has an rpm range of 435 to 900.

Motor DTP0036 has an rpm range of 300 to 900.

Motor DTP0036-50 has an rpm range of 300 to 900.

Motor DTP0054 has an rpm range of 438 to 900.

Motor DTP0054-50 has an rpm range of 358 to 900.

Motor EP00365 has an rpm range of 300 to 900.

Motor EP00545 has an rpm range of 436 to 900.

Motor GP0036 has an rpm range of 300 to 900.

Motor GP0036-50 has an rpm range of 300 to 900.

Motor GP0054 has an rpm range of 450 to 900.

Motor GP0054-50 has an rpm range of 360 to 900.