

R-AWPD-42-A

CFM	Static Pressure in Inches W.G.						
	0.000	0.250	0.500	0.750	1.000	1.250	1.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000		503 / 0.39	685 / 1.02	824 / 1.80	940 / 2.70	1043 / 3.70	1135 / 4.80
7000		571 / 0.55	760 / 1.32	905 / 2.25	1025 / 3.30	1130 / 4.45	
11000	428 / 0.21	652 / 0.83	826 / 1.68	970 / 2.73	1093 / 3.91		
15000	583 / 0.53	761 / 1.30	908 / 2.24	1040 / 3.37	1158 / 4.64		
19000	737 / 1.08	887 / 2.02	1012 / 3.08	1128 / 4.29			
23000	893 / 1.92	1022 / 3.05	1131 / 4.24				
27000	1048 / 3.11	1161 / 4.43					

Max Sizeable RPM = 1200 RPM. Table shown extended beyond this point for reference only.

Motor DHP00565 has an rpm range of 400 to 1150.

Motor DTP0056 has an rpm range of 400 to 1150.

Motor DTP0056-50 has an rpm range of 400 to 958.

Motor EP00565 has an rpm range of 400 to 1150.

Motor GP0056 has an rpm range of 400 to 1150.

Motor GP0056-50 has an rpm range of 400 to 958.