

R-AWPD-42-S

CFM	Static Pressure in Inches W.G.				
	0.000	0.125	0.250	0.375	0.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4000			384 / 0.52	444 / 0.86	493 / 1.25
6000		333 / 0.29	429 / 0.64	497 / 1.05	552 / 1.51
8000		371 / 0.40	462 / 0.78	537 / 1.24	597 / 1.75
10000	341 / 0.26	421 / 0.58	498 / 0.97	570 / 1.45	633 / 2.00
12000	409 / 0.45	477 / 0.83	541 / 1.25	605 / 1.74	665 / 2.31
14000	477 / 0.72	537 / 1.16	592 / 1.62	647 / 2.13	701 / 2.71
16000	544 / 1.07	598 / 1.58	647 / 2.09	695 / 2.64	743 / 3.23
18000	612 / 1.52	661 / 2.10	705 / 2.67	748 / 3.26	790 / 3.88
20000	680 / 2.09	725 / 2.73	765 / 3.36	804 / 4.00	842 / 4.67
22000	748 / 2.78	789 / 3.49	826 / 4.18		
24000	816 / 3.61				

Max Sizeable RPM = 850 RPM. Table shown extended beyond this point for reference only.

Motor 00509ET3E254T-W22 has an rpm range of 300 to 850.

Motor 00509ET3E254T-W22-50 has an rpm range of 300 to 730.

Motor DHP7/565 has an rpm range of 300 to 850.

Motor DTP7/56 has an rpm range of 300 to 850.

Motor DTP7/56-50 has an rpm range of 300 to 850.

Motor EP7/565 has an rpm range of 300 to 850.

Motor NP7/56 has an rpm range of 300 to 850.

Motor NP7/56-50 has an rpm range of 300 to 850.