

R-AWPD-48-A

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
5000		356 / 0.52	472 / 1.34	560 / 2.33	633 / 3.44	697 / 4.68	754 / 6.01	807 / 7.43	857 / 8.93
11000		419 / 0.76	550 / 1.74	647 / 2.95	725 / 4.33	794 / 5.84	854 / 7.46	909 / 9.19	
17000	355 / 0.48	489 / 1.25	607 / 2.32	707 / 3.63	792 / 5.15	866 / 6.82	931 / 8.64		
23000	480 / 1.17	584 / 2.13	678 / 3.31	766 / 4.71	848 / 6.30	923 / 8.07	991 / 10.00		
29000	605 / 2.35	691 / 3.50	768 / 4.84	841 / 6.35	913 / 8.04	982 / 9.88			
35000	730 / 4.14	804 / 5.47	869 / 6.99	932 / 8.66					
41000	855 / 6.65	920 / 8.18	977 / 9.88						

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.

Motor 00509ET3E254T-W22 has an rpm range of 300 to 880.

Motor 00509ET3E254T-W22-50 has an rpm range of 300 to 730.

Motor DHP01065 has an rpm range of 300 to 1000.

Motor DTP0106 has an rpm range of 300 to 1000.

Motor EP01065 has an rpm range of 300 to 1000.

Motor NP0106 has an rpm range of 300 to 1000.

Motor NP0106-50 has an rpm range of 300 to 958.