

RPTUB36-RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
14250	839 / 1.19	911 / 1.52	982 / 1.91	1053 / 2.35	1122 / 2.84	1189 / 3.38	1253 / 3.95	1313 / 4.55	1370 / 5.17
15950	939 / 1.66	1004 / 2.03	1068 / 2.45	1131 / 2.91	1194 / 3.42	1255 / 3.98	1315 / 4.58	1373 / 5.21	1429 / 5.87
17650	1039 / 2.26	1097 / 2.66	1155 / 3.10	1213 / 3.59	1270 / 4.12	1327 / 4.70	1382 / 5.31	1437 / 5.97	1490 / 6.65
19350	1139 / 2.97	1192 / 3.41	1245 / 3.89	1298 / 4.40	1350 / 4.95	1402 / 5.55	1454 / 6.18	1505 / 6.86	
21050	1239 / 3.82	1288 / 4.30	1337 / 4.81	1386 / 5.35	1434 / 5.93	1482 / 6.55	1529 / 7.20		
22750	1339 / 4.83	1384 / 5.34	1430 / 5.88	1475 / 6.45	1520 / 7.06				
24450	1439 / 5.99	1481 / 6.54	1524 / 7.12						
26150	1539 / 7.33								

Max Sizeable RPM = 1600 RPM. Table shown extended beyond this point for reference only.

Catalog #109R
March 2009