

**RPTUB42-RA**

CFM	Static Pressure in Inches W.G.								
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
15370	580 / 0.97	651 / 1.37	713 / 1.81	772 / 2.29	826 / 2.81	878 / 3.37	927 / 3.97	974 / 4.60	1018 / 5.26
17240	651 / 1.37	714 / 1.82	772 / 2.29	826 / 2.81	877 / 3.36	925 / 3.95	972 / 4.57	1016 / 5.23	1059 / 5.92
19110	721 / 1.87	779 / 2.36	833 / 2.88	883 / 3.42	930 / 4.01	976 / 4.63	1020 / 5.28	1062 / 5.96	1103 / 6.68
20980	792 / 2.47	845 / 3.01	895 / 3.57	941 / 4.16	986 / 4.77	1029 / 5.42	1070 / 6.10	1110 / 6.82	
22850	862 / 3.19	912 / 3.77	958 / 4.38	1002 / 5.01	1044 / 5.66	1084 / 6.34	1123 / 7.06		
24720	932 / 4.04	979 / 4.67	1022 / 5.32	1063 / 5.99	1103 / 6.68	1141 / 7.40			
26590	1003 / 5.03	1046 / 5.70	1087 / 6.40	1126 / 7.11					
28460	1073 / 6.16	1114 / 6.89							
30330	1144 / 7.46								

**Max Sizeable RPM = 1175 RPM. Table shown extended beyond this point for reference only.**

Catalog #109R

March 2009