

RPTUB48-RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
19930	492 / 1.05	567 / 1.61	632 / 2.23	688 / 2.87	739 / 3.56	787 / 4.30			
22720	561 / 1.56	628 / 2.18	688 / 2.87	741 / 3.59	789 / 4.33	834 / 5.11	876 / 5.94	917 / 6.81	
25510	630 / 2.20	690 / 2.89	746 / 3.66	796 / 4.45	842 / 5.26	884 / 6.09	924 / 6.96	963 / 7.87	1000 / 8.82
28300	699 / 3.00	753 / 3.76	805 / 4.60	853 / 5.46	896 / 6.35	937 / 7.25	975 / 8.18	1012 / 9.13	
31090	767 / 3.98	817 / 4.81	865 / 5.71	910 / 6.65	952 / 7.61	991 / 8.58	1028 / 9.58		
33880	836 / 5.15	882 / 6.04	927 / 7.02	969 / 8.03	1009 / 9.06				
36670	905 / 6.53	947 / 7.49	989 / 8.53	1029 / 9.61					
39460	974 / 8.14	1013 / 9.16							
42250	1042 / 9.99								

Max Sizeable RPM = 1075 RPM. Table shown extended beyond this point for reference only.

Catalog #109R  
March 2009