

Max Sizeable RPM = 2000 RPM. Curve shown extended beyond this point for reference only.

Motor BMN48-375I1-50-115 has an rpm range of 300 to 1800.

Motor BMN48-375I1-60-115 has an rpm range of 300 to 1800.

Motor BMN48-375I2-50-230/277 has an rpm range of 300 to 1800.

Motor BMN48-375I2-60-230/277 has an rpm range of 300 to 1800.

Motor CK48BS20HF01-50 has an rpm range of 431 to 1425.

Motor CK48BS20HF01-60 has an rpm range of 431 to 1725.

Motor CK48BS21HF01-60 has an rpm range of 431 to 1400.

Motor CK48HF21HF01-50-115 has an rpm range of 1100 to 1425.

Motor CK48HF2 IHF0 1-50-115 has an rpm range of 1100 to 1425

Motor CK48HF21HF01-50-230 has an rpm range of 1100 to 1425.

Motor CK48HF21HF01-60-115 has an rpm range of 1100 to 1670.

Motor CK48HF21HF01-60-230 has an rpm range of 1100 to 1670.

Performance shown is certified for Installation Type A: Free outlet. Speed shown is nominal. Performance is based on actual speed of test. Performance ratings do not include the effects of appurtenances (accessories).

Catalog #113R October 2019