

BDCR18HPRA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
2300	907 11.9 / 0.38	987 12.2 / 0.53	1062 12.7 / 0.69	1134 13.5 / 0.86	1204 14.2 / 1.04	1272 15.0 / 1.24	1337 15.9 / 1.44	1401 16.9 / 1.65	1461 17.8 / 1.87
2620	1034 15.1 / 0.57	1105 15.2 / 0.74	1171 15.2 / 0.91	1235 15.6 / 1.10	1298 16.4 / 1.29	1360 17.2 / 1.50	1420 18.1 / 1.72	1479 19.0 / 1.94	
2940	1160 18.1 / 0.80	1223 17.9 / 0.99	1284 17.9 / 1.19	1342 18.4 / 1.39	1399 19.1 / 1.60	1455 19.8 / 1.82			
3260	1287 21 / 1.09	1344 21 / 1.30	1399 21 / 1.52	1452 21 / 1.74					
3580	1413 24 / 1.45	1465 24 / 1.68							

Max Sizeable RPM = 1500 RPM. Table shown extended beyond this point for reference only.