

**BDCR36HPRA**

CFM	Static Pressure in Inches W.G.							
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500
	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
5500	335 8.2 / 0.42	444 13.2 / 1.21	541 18.4 / 2.19	625 24 / 3.30	700 31 / 4.52	768 38 / 5.83	831 43 / 7.23	889 48 / 8.71
6500	396 11.0 / 0.70	489 15.4 / 1.58	576 20 / 2.65	655 26 / 3.87	726 31 / 5.19	791 37 / 6.60	852 43 / 8.09	909 48 / 9.66
7500	457 14.1 / 1.07	538 18.2 / 2.06	616 23 / 3.23	689 28 / 4.54	756 34 / 5.96	819 38 / 7.47	877 43 / 9.06	
8500	518 17.4 / 1.55	590 21 / 2.66	660 26 / 3.92	727 31 / 5.33	790 36 / 6.84	849 40 / 8.45		
9500	579 21 / 2.17	643 25 / 3.38	707 30 / 4.75	768 35 / 6.24	827 38 / 7.85	883 42 / 9.56		
10500	640 25 / 2.93	698 29 / 4.25	756 34 / 5.71	813 38 / 7.31	867 41 / 9.01			
11500	700 29 / 3.84	754 34 / 5.28	807 37 / 6.85	859 41 / 8.54				
12500	761 34 / 4.94	810 37 / 6.49	859 41 / 8.16	908 44 / 9.95				
13500	822 38 / 6.22	867 41 / 7.89	913 44 / 9.67					
14500	883 42 / 7.70	925 45 / 9.49						
15500	944 46 / 9.41							

Max Sizeable RPM = 950 RPM. Table shown extended beyond this point for reference only.