

RABI11BD-RM

CFM	Discharge Velocity FPM	Static Pressure in Inches W.G.					
		0.000	0.500	1.000	1.500	2.000	2.500
		RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
1000	1543	1159 6.4 / 0.11	1473 8.9 / 0.23	1706 11.4 / 0.36	1912 14.0 / 0.50	2101 16.5 / 0.66	2283 19.0 / 0.84
1250	1929	1448 9.4 / 0.21	1715 12.3 / 0.36	1929 14.2 / 0.52	2111 16.6 / 0.68	2281 19.0 / 0.85	
1500	2314	1736 13.1 / 0.35	1966 15.7 / 0.54	2165 18.1 / 0.73	2333 19.7 / 0.92		
1750	2700	2025 17.1 / 0.56	2226 19.4 / 0.78				
2000	3086	2315 21 / 0.84					

Max Sizeable RPM = 2400 RPM. Table shown extended beyond this point for reference only.

Max discharge velocity for restaurant applications is 1800 fpm. This equates to 1167 cfm.

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Power rating (BHP) does not include transmission losses. The sound ratings shown are loudness values in fan sones at 5 ft (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for Installation Type B: ducted outlet hemispherical sone levels. Ratings do not include the effect of duct end correction.

Catalog #110R
December 2013