

RABI11BDHP-RM

CFM	Discharge Velocity FPM	Static Pressure in Inches W.G.					
		0.000	0.500	1.000	1.500	2.000	2.500
		RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
840	1296	1217 7.4 / 0.12	1511 9.2 / 0.23	1754 11.2 / 0.35	1967 13.6 / 0.49	2159 15.9 / 0.65	2340 18.3 / 0.82
1070	1651	1551 11.4 / 0.24	1792 13.2 / 0.38	2000 14.8 / 0.52	2188 16.7 / 0.68	2362 18.9 / 0.85	
1300	2006	1884 15.9 / 0.43	2090 17.7 / 0.60	2273 19.4 / 0.77			
1530	2361	2217 21 / 0.70	2398 23 / 0.90				

Max Sizeable RPM = 2400 RPM. Table shown extended beyond this point for reference only.

Max discharge velocity for restaurant applications is 1800 fpm. This equates to 1167 cfm.

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Power rating (BHP) does not include transmission losses. The sound ratings shown are loudness values in fan sones at 5 ft (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for Installation Type B: ducted outlet hemispherical sone levels. Ratings do not include the effect of duct end correction.

Catalog #110R
December 2013