

RABI11BDHP-RM

CFM	Discharge Velocity FPM	Static Pressure in Inches W.G.					
		0.000	0.500	1.000	1.500	2.000	2.500
		RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
840	1296	1217 7.4 / 0.12	1511 9.2 / 0.23	1754 11.2 / 0.35	1967 13.6 / 0.49	2159 15.9 / 0.65	2340 18.3 / 0.82
1070	1651	1551 11.4 / 0.24	1792 13.2 / 0.38	2000 14.8 / 0.52	2188 16.7 / 0.68	2362 18.9 / 0.85	
1300	2006	1884 15.9 / 0.43	2090 17.7 / 0.60	2273 19.4 / 0.77			
1530	2361	2217 21 / 0.70	2398 23 / 0.90				

Max Sizeable RPM = 2400 RPM. Table shown extended beyond this point for reference only.

Max discharge velocity for restaurant applications is 1800 fpm. This equates to 1167 cfm.

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Power rating (BHP) does not include transmission losses.

The sound ratings shown are loudness values in hemispherical sones at 1.5m (5ft) in a hemispherical free field calculated per ANSI/AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels. Ratings do not include the effect of duct end correction.

RuppAir certifies that Model RABI11BDHP-RM shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and Publication 311, and comply with the requirements of the AMCA Certified Rating Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC) Title 20 Regulations.

Catalog #110R
November 2024

