

RABI13BDHP-RM

CFM	Discharge Velocity FPM	Static Pressure in Inches W.G.					
		0.000	0.500	1.000	1.500	2.000	2.500
		RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
1100	1025	1099 8.7 / 0.13	1341 9.2 / 0.25	1547 11.0 / 0.38	1732 13.0 / 0.54	1900 15.2 / 0.70	2037 17.1 / 0.86
1500	1398	1497 14.5 / 0.34	1687 14.7 / 0.50	1852 16.0 / 0.66	2005 17.6 / 0.84	2149 19.2 / 1.03	
1900	1771	1896 22 / 0.69	2052 21 / 0.89	2189 22 / 1.08			

Max Sizeable RPM = 2200 RPM. Table shown extended beyond this point for reference only.

Max discharge velocity for restaurant applications is 1800 fpm. This equates to 1932 cfm.

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Power rating (BHP) does not include transmission losses. The sound ratings shown are loudness values in fan sones at 5 ft (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for Installation Type B: ducted outlet hemispherical sone levels. Ratings do not include the effect of duct end correction.

Catalog #110R
December 2013