

## RABI15BDHP-RM

CFM	Discharge Velocity FPM	Static Pressure in Inches W.G.							
		0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500
		RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP	RPM Sone/BHP
1400	1067	1059 8.4 / 0.16	1281 10.1 / 0.31	1478 12.7 / 0.48	1651 15.0 / 0.67	1806 17.4 / 0.87	1947 19.7 / 1.09	2077 22 / 1.31	2198 24 / 1.54
1900	1448	1437 13.6 / 0.41	1603 14.4 / 0.61	1763 16.8 / 0.82	1911 19.1 / 1.05	2047 21 / 1.28	2176 24 / 1.54		
2400	1829	1814 19.4 / 0.82	1946 20 / 1.07	2078 22 / 1.33					
2900	2210	2194 26 / 1.45							

**Max Sizeable RPM = 2200 RPM. Table shown extended beyond this point for reference only.**

**Max discharge velocity for restaurant applications is 1800 fpm. This equates to 2362 cfm.**

Performance shown is certified for Installation Type B: Free inlet, Ducted outlet. Performance ratings do not include the effects of appurtenances (accessories). Power rating (BHP) does not include transmission losses.

The sound ratings shown are loudness values in hemispherical sones at 1.5m (5ft) in a hemispherical free field calculated per ANSI/AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels. Ratings do not include the effect of duct end correction.

RuppAir certifies that Model RABI15BDHP-RM shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and Publication 311, and comply with the requirements of the AMCA Certified Rating Program. Tested to AMCA Standards 210 and 300. Meets California Energy Commission (CEC) Title 20 Regulations.

Catalog #110R  
November 2024

