

**R76**

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
600	769 / 0.07	971 / 0.13	1215 / 0.24	1442 / 0.39	1626 / 0.55	1775 / 0.71	1905 / 0.87	2020 / 1.02	2128 / 1.18
700	896 / 0.11	1065 / 0.17	1261 / 0.27	1477 / 0.43	1671 / 0.61	1832 / 0.80	1972 / 0.98	2096 / 1.17	2201 / 1.34
800	1024 / 0.17	1171 / 0.23	1331 / 0.32	1515 / 0.47	1702 / 0.66	1874 / 0.87	2020 / 1.08	2156 / 1.30	2273 / 1.50
900	1152 / 0.24	1282 / 0.31	1420 / 0.40	1573 / 0.53	1737 / 0.71	1903 / 0.92	2059 / 1.15	2200 / 1.40	2326 / 1.64
1000	1280 / 0.33	1397 / 0.40	1517 / 0.49	1647 / 0.62	1792 / 0.78	1942 / 0.99	2092 / 1.22	2227 / 1.46	2364 / 1.74
1100	1408 / 0.44	1515 / 0.51	1622 / 0.61	1735 / 0.73	1858 / 0.88	1993 / 1.07	2128 / 1.30	2263 / 1.55	2397 / 1.83
1200	1536 / 0.57	1635 / 0.65	1732 / 0.75	1832 / 0.86	1942 / 1.01	2058 / 1.19	2178 / 1.40	2303 / 1.65	
1300	1665 / 0.73	1754 / 0.81	1844 / 0.91	1937 / 1.03	2031 / 1.17	2135 / 1.34	2241 / 1.54	2355 / 1.77	
1400	1793 / 0.91	1877 / 1.00	1961 / 1.10	2044 / 1.22	2131 / 1.36	2222 / 1.53	2318 / 1.71		
1500	1921 / 1.12	2000 / 1.21	2078 / 1.32	2155 / 1.44	2235 / 1.59	2318 / 1.75			
1600	2049 / 1.36	2122 / 1.46	2195 / 1.57	2266 / 1.69	2343 / 1.84				
1700	2177 / 1.63	2246 / 1.73	2313 / 1.85	2384 / 1.98					
1800	2305 / 1.93								

Max Sizeable RPM = 2400 RPM. Table shown extended beyond this point for reference only.