

R76

| CFM | Static Pressure in Inches W.G. | | | | | |
|-----|--------------------------------|-------------|-------------|-------------|-------------|-------------|
| | 0.000 | 0.125 | 0.250 | 0.375 | 0.500 | 0.625 |
| | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP | RPM/BHP |
| 650 | 1290 / 0.32 | 1377 / 0.39 | 1471 / 0.48 | 1566 / 0.57 | 1671 / 0.70 | 1786 / 0.85 |
| 700 | 1389 / 0.40 | 1471 / 0.48 | 1556 / 0.56 | 1643 / 0.66 | 1737 / 0.78 | 1837 / 0.93 |
| 750 | 1488 / 0.49 | 1556 / 0.56 | 1641 / 0.66 | 1724 / 0.77 | 1812 / 0.89 | |
| 800 | 1587 / 0.60 | 1656 / 0.68 | 1732 / 0.78 | 1806 / 0.88 | | |
| 850 | 1687 / 0.72 | 1753 / 0.80 | 1820 / 0.90 | | | |
| 900 | 1786 / 0.85 | 1848 / 0.94 | | | | |

Max Sizeable RPM = 1884 RPM. Table shown extended beyond this point for reference only.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 1200 to 1800.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 1200 to 1800.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 1200 to 1800.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 1200 to 1800.