





MODEL NO	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	U	V	W	X	Y	Z	AA	BB	CC	DD	EE	FF	GG	**FA FILTER QUANTITY	**FA FILTER/HOOD QUANTITY	**RA FILTER QUANTITY
12M	70	46	38	5.5	30	1	39.25	8.5	18.75	8.5	18.75	30.25	39.5	48	51.66	27	10	19	19	10	24	4.5	11.5	4.5	29.5	11.75	24.25	29.75	39.5	30	(4)20"x25"	(4)20"x25"	(4)20"x25"
15M	70	46	38	5.5	30	1	39.25	8.5	18.75	8.5	18.75	30.25	39.5	48	51.66	27	10	19	19	10	24	4.5	11.5	4.5	29.5	11.75	24.25	29.75	39.5	30	(4)20"x25"	(4)20"x25"	(4)20"x25"



- ▲ A 80/20 BURNER PROFILE
- ▲ B FC DWDI BLOWER
- ▲ C LIFT-OFF INTAKE FILTER SERVICE DOOR
- ▲ D DAMPER MOTOR
- ▲ E ELEC/MANIFOLD CONTROLS VESTIBULE
- ▲ F HINGED SERVICE DOOR
- ▲ G MAIN DISCONNECT SWITCH
- ▲ H SUPPLY FAN BLOWER MOTOR
- ▲ J STANDARD FRESH AIR INTAKE HOOD/FILTER COMBINATION (FILTERS SUPPLIED ONLY WHEN ORDERED)
- ▲ K FRESH AIR INTAKE FILTER
- ▲ L FRESH AIR INTAKE DAMPER
- ▲ M FRESH AIR INTAKE OPENING
- ▲ N RETURN AIR INTAKE OPENING
- ▲ P GAS CONNECTION
- ▲ R LIFTING LUG
- ▲ S DISCHARGE DAMPER
- ▲ T DISCHARGE DIFFUSER
- ▲ U RETURN AIR INTAKE FILTER
- ▲ V RETURN AIR INTAKE FILTER SCREEN



NOTES:
 - 1 INCH CONNECTION FLANGE SUPPLIED AROUND FRESH AIR INTAKE OPENING
 - (4) LIFTING LUGS AVAILABLE IN HANGING CONFIGURATION
 - DISCHARGE DIFFUSER SUPPLIED WITH ADJUSTABLE BLADES
 - GRIDDLE SUPPORT RECOMMENDED UNDER RETURN AIR INTAKE FILTER
 - BASE DESIGNED FOR FLAT MOUNT OR CURB MOUNT
 - **F : FRESH AIR
 - **RA : RETURN AIR

RUPP AIR
MANAGEMENT SYSTEMS

MATERIAL: _____
 SCALE: 1 to 1
 DO NOT SCALE DRAWING USE DIMENSIONS SHOWN
 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED

DRAWN BY: TKL
 DATE: 02/10/00
 APPROVED BY: _____
 DATE: _____

REV	TITLE	REVISION DESCRIPTION	ECH NO	DWG	DATE

RAM-12M AND 15M
ARRANGEMENT H2 DOWN DISCHARGE

REVISION: LATEST SHOWN
75000040C
 30400002

TOLERANCES:
 2 PLCS ±.03
 3 PLCS ±.015