

INSA10RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	358 / 0.06	572 / 0.12	741 / 0.20	894 / 0.30	1029 / 0.41	1147 / 0.52	1250 / 0.63	1340 / 0.72	
1200	429 / 0.10	618 / 0.17	768 / 0.25	902 / 0.35	1034 / 0.47	1152 / 0.60	1261 / 0.74	1357 / 0.87	1448 / 1.00
1400	501 / 0.15	669 / 0.24	806 / 0.33	930 / 0.43	1034 / 0.54	1158 / 0.68	1264 / 0.83	1363 / 0.99	1455 / 1.15
1600	572 / 0.23	721 / 0.32	851 / 0.43	964 / 0.54	1071 / 0.65	1173 / 0.79	1272 / 0.94	1368 / 1.10	1459 / 1.27
1800	644 / 0.32	777 / 0.43	900 / 0.55	1006 / 0.67	1104 / 0.79	1198 / 0.92	1290 / 1.07	1379 / 1.23	1466 / 1.41
2000	715 / 0.44	834 / 0.56	951 / 0.69	1052 / 0.82	1145 / 0.95	1232 / 1.09	1318 / 1.24	1401 / 1.40	1481 / 1.57
2200	786 / 0.59	893 / 0.71	1003 / 0.86	1101 / 1.00	1189 / 1.14	1272 / 1.29	1351 / 1.44	1429 / 1.61	1505 / 1.78
2400	858 / 0.77	954 / 0.89	1058 / 1.05	1151 / 1.21	1236 / 1.37	1316 / 1.52	1391 / 1.68	1464 / 1.85	

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.