

INSA10RA

CFM	Static Pressure in Inches W.G.							
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	399 / 0.05	539 / 0.12	640 / 0.21	728 / 0.31	812 / 0.43	895 / 0.57	976 / 0.74	1053 / 0.93
1200	479 / 0.09	601 / 0.17	697 / 0.27	777 / 0.37	850 / 0.49	922 / 0.62	992 / 0.78	1061 / 0.95
1400	558 / 0.14	663 / 0.23	758 / 0.35	833 / 0.46	901 / 0.58	965 / 0.72	1026 / 0.86	
1600	638 / 0.21	728 / 0.31	819 / 0.44	893 / 0.57	958 / 0.70	1017 / 0.84	1073 / 0.98	
1800	717 / 0.29	794 / 0.40	881 / 0.55	954 / 0.69	1017 / 0.84	1074 / 0.99		
2000	797 / 0.40	864 / 0.51	944 / 0.67	1016 / 0.84				
2200	876 / 0.54	935 / 0.65	1009 / 0.82					
2400	956 / 0.70	1009 / 0.82	1074 / 0.99					

Max Sizeable RPM = 1075 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-750I2-50-230/277 has an rpm range of 370 to 1075.

Motor BMN48-750I2-60-230/277 has an rpm range of 370 to 1075.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 370 to 1075.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 370 to 1075.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 370 to 1075.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 370 to 1075.