

## INSA10RAL

CFM	Static Pressure in Inches W.G.				
	0.000	0.125	0.250	0.375	0.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	399 / 0.05	539 / 0.12	640 / 0.21	728 / 0.31	812 / 0.43
1200	479 / 0.09	601 / 0.17	697 / 0.27	777 / 0.37	
1400	558 / 0.14	663 / 0.23	758 / 0.35		
1600	638 / 0.21	728 / 0.31	819 / 0.44		
1800	717 / 0.29	794 / 0.40			
2000	797 / 0.40				

**Max Sizeable RPM = 825 RPM. Table shown extended beyond this point for reference only.**

Motor BMN48-750I2-50-230/277 has an rpm range of 370 to 825.

Motor BMN48-750I2-60-230/277 has an rpm range of 370 to 825.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 370 to 825.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 370 to 825.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 370 to 825.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 370 to 825.