

INSA12RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2250	420 / 0.25	549 / 0.34	673 / 0.46	783 / 0.59	884 / 0.72	977 / 0.86			
2500	467 / 0.34	582 / 0.44	698 / 0.57	803 / 0.71	898 / 0.85	987 / 1.00	1071 / 1.15		
2750	513 / 0.45	617 / 0.56	725 / 0.70	824 / 0.85	916 / 1.00	1001 / 1.16	1082 / 1.32	1159 / 1.49	1232 / 1.66
3000	560 / 0.59	654 / 0.70	754 / 0.85	849 / 1.01	936 / 1.17	1018 / 1.34	1096 / 1.51	1170 / 1.69	1241 / 1.87
3250	607 / 0.75	692 / 0.86	785 / 1.02	875 / 1.19	959 / 1.37	1038 / 1.55	1113 / 1.73	1184 / 1.91	1253 / 2.10
3500	653 / 0.93	732 / 1.05	818 / 1.22	903 / 1.40	984 / 1.59	1060 / 1.78	1132 / 1.97	1202 / 2.17	1268 / 2.36
3750	700 / 1.15	773 / 1.27	853 / 1.44	933 / 1.63	1010 / 1.83	1084 / 2.04	1153 / 2.24	1220 / 2.45	1285 / 2.66
4000	746 / 1.39	814 / 1.53	889 / 1.70	964 / 1.90	1038 / 2.11	1109 / 2.32	1176 / 2.54	1241 / 2.76	1304 / 2.98

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.