

INSA15RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2750	407 / 0.39	484 / 0.53	582 / 0.69	683 / 0.86	765 / 1.06	836 / 1.28			
3000	444 / 0.51	513 / 0.65	598 / 0.83	694 / 1.01	779 / 1.21	851 / 1.43	915 / 1.68		
3250	481 / 0.65	545 / 0.80	618 / 0.98	707 / 1.18	792 / 1.38	862 / 1.60	930 / 1.85	989 / 2.12	1044 / 2.41
3500	518 / 0.81	577 / 0.97	642 / 1.16	721 / 1.37	803 / 1.59	879 / 1.81	945 / 2.06	1004 / 2.33	1058 / 2.61
3750	555 / 0.99	610 / 1.16	669 / 1.37	738 / 1.59	816 / 1.82	891 / 2.05	958 / 2.30	1019 / 2.56	1074 / 2.85
4000	592 / 1.21	643 / 1.38	697 / 1.59	759 / 1.83	830 / 2.07	903 / 2.31	971 / 2.57	1033 / 2.84	1088 / 3.12

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.