



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	UNIT DIMENSIONS										CURB	DISCHARGE OPENING				RETURN OPENING								
	A	B	BB	C	CC	D	DD	E	EE	F		G	H	J	K	L	N	P	R	S	T	U	V	X
D.250-G10	148-7/8	27-3/8	36-3/4	29-3/4	36-3/4	26-1/16	33	3-3/4	3-3/4	53-5/8	7-13/16	34-13/16	21	71	102-7/16	13-1/4	11-1/2	3-7/8	1-3/4	14	8	14	12-1/2	18
D.500-G10	148-7/8	27-3/8	36-3/4	29-3/4	36-3/4	26-1/16	33	3-3/4	3-3/4	53-5/8	7-13/16	34-13/16	21	71	102-7/16	13-1/4	11-1/2	3-7/8	1-3/4	14	8	14	12-1/2	18
D.250-G15	162-7/8	37-3/8	40-3/4	36-3/4	43-3/8	38-1/8	33	3-3/4	5-1/4	51-5/8	7-13/16	42-13/16	31	79	115-7/16	18-3/4	16	6-1/8	5-1/2	22-3/4	8	11	7-1/2	24
D.500-G15	162-7/8	37-3/8	40-3/4	36-3/4	43-3/8	38-1/8	33	3-3/4	5-1/4	51-5/8	7-13/16	42-13/16	31	79	115-7/16	18-3/4	16	6-1/8	5-1/2	22-3/4	8	11	7-1/2	24
D.750-G15	162-7/8	37-3/8	40-3/4	36-3/4	43-3/8	38-1/8	33	3-3/4	5-1/4	51-5/8	7-13/16	42-13/16	31	79	115-7/16	18-3/4	16	6-1/8	5-1/2	22-3/4	8	11	7-1/2	24
D.500-G18	165	41-3/8	47-7/8	43-3/8	51-3/8	38-1/16	46-1/8	5-1/4	5-1/4	76-3/8	9-1/2	47-13/16	35	84	123-7/16	22	19	6-1/2	7	28	8	7	4-1/2	30
D.1000-G18	165	41-3/8	47-7/8	43-3/8	51-3/8	38-1/16	46-1/8	5-1/4	5-1/4	76-3/8	9-1/2	47-13/16	35	84	123-7/16	22	19	6-1/2	7	28	8	7	4-1/2	30
D.1000-920	208-3/16	48-7/8	51-3/8	46-1/8	53-1/8	46-1/8	53-1/8	5-1/4	5-1/4	71-3/8	13-9/16	66-5/16	42	115-3/16	153-3/16	24-7/8	24-7/8	8-9/16	1-1/8	33	10	11	8	36
D.2000-920	218-3/16	55-5/8	58-3/8	46-1/8	53-1/8	46-1/8	53-1/8	5-1/4	5-1/4	71-3/8	13-9/16	66-5/16	42	115-3/16	153-3/16	24-7/8	24-7/8	8-9/16	1-1/8	33	10	11	8	36
D.2000-925	218-3/16	55-5/8	58-3/8	46-1/8	53-1/8	46-1/8	53-1/8	5-1/4	5-1/4	71-3/8	13-9/16	66-5/16	42	115-3/16	153-3/16	24-7/8	24-7/8	8-9/16	1-1/8	33	10	11	8	36
D.2000-925	218-3/16	55-5/8	58-3/8	46-1/8	53-1/8	46-1/8	53-1/8	5-1/4	5-1/4	71-3/8	13-9/16	66-5/16	42	115-3/16	153-3/16	24-7/8	24-7/8	8-9/16	1-1/8	33	10	11	8	36
D.2000-925	218-3/16	55-5/8	58-3/8	46-1/8	53-1/8	46-1/8	53-1/8	5-1/4	5-1/4	71-3/8	13-9/16	66-5/16	42	115-3/16	153-3/16	24-7/8	24-7/8	8-9/16	1-1/8	33	10	11	8	36

MODEL	BTU RANGE (QBHD)		GAS PRESSURE		GAS CONNECTION		CELDEK EVAPORATIVE COOLING UNIT		INTAKE HOOD		WATER INLET		DRAIN OPENING		OPTIONAL MIXING BOX FILTERS	
	BTU LOW	BTU HIGH	MIN.	MAX.	"T"	(QWP)	TOT. WEIGHT	MEDIA SIZE & QTY	MAX. FLOW RATE	FILTER SIZE & QTY	AA	AB	AC	AD	FILTER SIZE & QTY	
D.250-G10	6'	18	7" W.C.	14" W.C.	3/4"		945	LBS	25"x32"x12"	20	6.5	GPH	4-1/2	18	10"x16"x2"	(2)
D.500-G10	12'	18	7" W.C.	14" W.C.	3/4"		950	LBS	25"x32"x12"	20	6.5	GPH	4-1/2	18	10"x16"x2"	(2)
D.250-G15	6'	18	27/5" W.C.	14" W.C.	1		1310	LBS	30"x36"x12"	28	8.4	GPH	4-1/2	20	15"x20"x2"	(1)
D.500-G15	12'	18	27/5" W.C.	14" W.C.	1		1315	LBS	30"x36"x12"	28	8.4	GPH	4-1/2	20	15"x20"x2"	(1)
D.750-G15	12'	18	27/5" W.C.	14" W.C.	1		1320	LBS	30"x36"x12"	28	8.4	GPH	4-1/2	20	15"x20"x2"	(1)
D.500-G18	12'	18	27/5" W.C.	14" W.C.	1		1670	LBS	38"x43"x12"	35	10.15	GPH	4-1/2	20	15"x20"x2"	(1)
D.750-G18	12'	18	27/5" W.C.	14" W.C.	1		1675	LBS	38"x43"x12"	35	10.15	GPH	4-1/2	20	15"x20"x2"	(1)
D.1000-G18	24'	36.6	7" W.C.	14" W.C.	1		1690	LBS	38"x43"x12"	35	10.15	GPH	4-1/2	20	15"x20"x2"	(1)
D.1000-920	24'	36.6	7" W.C.	14" W.C.	1-1/4"		2490	LBS	45"x54"x12"	42	12.6	GPH	4-1/2	20	15"x20"x2"	(2)
D.1500-920	30'	45.8	7" W.C.	5 PSI	1-1/4"		3205	LBS	45"x54"x12"	42	12.6	GPH	4-1/2	20	15"x20"x2"	(2)
D.2000-925	48'	73.3	2200	5 PSI	1-1/2"		3235	LBS	45"x54"x12"	57	20.1	GPH	4-1/2	20	15"x20"x2"	(2)
D.2500-925	60'	91.6	2750	5 PSI	1-1/2"		3250	LBS	45"x54"x12"	57	20.1	GPH	4-1/2	20	15"x20"x2"	(2)

GENERAL CONSTRUCTION: Profile plates shall be formed from G90 galvanized steel. Profile plates shall vary in size per unit. Profile plates shall be mounted along the same plane as the discharge of the burner. Profile design shall incorporate proper torque for mounting. Profile design shall incorporate proper torque for mounting. Profile design shall incorporate proper torque for mounting.

