

R1D.250-G10

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1750	639 / 0.31	821 / 0.45	965 / 0.60	1091 / 0.76	1209 / 0.93	1323 / 1.12	1432 / 1.32	1536 / 1.54	1636 / 1.77
2000	730 / 0.46	892 / 0.62	1030 / 0.79	1147 / 0.97	1255 / 1.15	1359 / 1.34	1459 / 1.55	1558 / 1.78	
2250	821 / 0.65	966 / 0.83	1098 / 1.03	1210 / 1.22	1310 / 1.42	1406 / 1.62	1499 / 1.84		
2500	913 / 0.90	1042 / 1.08	1168 / 1.31	1275 / 1.52	1371 / 1.74	1462 / 1.96			
2750	1004 / 1.20	1120 / 1.39	1239 / 1.64	1343 / 1.88					
3000	1095 / 1.55	1200 / 1.76							

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Max listed CFM for Recirculating Direct Fired Heaters : A1 = 2500