

**R4D.1500-920**

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
8000	376 / 1.31	448 / 1.83	506 / 2.31	563 / 2.81	620 / 3.35	676 / 3.92	730 / 4.50	781 / 5.10	830 / 5.70	876 / 6.32	919 / 6.95	961 / 7.59	1000 / 8.23
9000	423 / 1.87	490 / 2.46	542 / 2.99	593 / 3.55	644 / 4.13	695 / 4.73	745 / 5.36	793 / 6.01	840 / 6.68	885 / 7.35	928 / 8.04	970 / 8.73	1009 / 9.43
10000	470 / 2.56	533 / 3.23	581 / 3.83	627 / 4.43	673 / 5.05	718 / 5.70	764 / 6.38	809 / 7.07	854 / 7.78	897 / 8.51	939 / 9.25	979 / 10.00	
11000	517 / 3.40	576 / 4.16	621 / 4.82	663 / 5.48	705 / 6.15	747 / 6.84	788 / 7.55	830 / 8.29	871 / 9.05	912 / 9.82			
12000	564 / 4.42	620 / 5.26	663 / 5.99	702 / 6.70	740 / 7.42	778 / 8.16	816 / 8.92	854 / 9.70					
13000	611 / 5.62	664 / 6.55	705 / 7.34	742 / 8.12	777 / 8.89	813 / 9.68							

Max Sizeable RPM = 1100 RPM. Table shown extended beyond this point for reference only.

Max listed CFM for Recirculating Direct Fired Heaters : A4 = 11000