

**R5D.2000-925**

| CFM   | Static Pressure in Inches W.G. |             |             |             |             |             |             |
|-------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|
|       | 0.000                          | 0.500       | 1.000       | 1.500       | 2.000       | 2.500       | 3.000       |
|       | RPM/BHP                        | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     |
| 10000 | 260 / 1.21                     | 456 / 3.16  | 587 / 5.09  | 696 / 7.18  | 788 / 9.32  | 867 / 11.43 | 935 / 13.52 |
| 11000 | 286 / 1.61                     | 473 / 3.79  | 598 / 5.85  | 706 / 8.09  | 799 / 10.43 | 879 / 12.77 | 950 / 15.10 |
| 12000 | 312 / 2.09                     | 490 / 4.50  | 612 / 6.71  | 716 / 9.09  | 808 / 11.60 | 890 / 14.15 | 963 / 16.71 |
| 13000 | 338 / 2.66                     | 509 / 5.32  | 626 / 7.68  | 727 / 10.19 | 818 / 12.85 | 900 / 15.59 | 974 / 18.36 |
| 14000 | 364 / 3.32                     | 528 / 6.23  | 642 / 8.77  | 740 / 11.40 | 828 / 14.19 | 909 / 17.10 |             |
| 15000 | 389 / 4.09                     | 547 / 7.25  | 659 / 9.98  | 753 / 12.74 | 840 / 15.66 | 919 / 18.72 |             |
| 16000 | 415 / 4.96                     | 567 / 8.38  | 676 / 11.32 | 768 / 14.23 | 852 / 17.27 |             |             |
| 17000 | 441 / 5.95                     | 586 / 9.62  | 694 / 12.79 | 784 / 15.86 | 865 / 19.03 |             |             |
| 18000 | 467 / 7.06                     | 606 / 10.98 | 713 / 14.39 | 800 / 17.63 |             |             |             |
| 19000 | 493 / 8.30                     | 626 / 12.45 | 731 / 16.14 | 818 / 19.56 |             |             |             |
| 20000 | 519 / 9.69                     | 646 / 14.06 | 751 / 18.03 |             |             |             |             |
| 21000 | 545 / 11.21                    | 666 / 15.80 |             |             |             |             |             |

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.

Max listed CFM for Recirculating Direct Fired Heaters : A5 = 18000