

R5D.2500-925

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
10000	260 / 1.21	375 / 2.25	456 / 3.16	524 / 4.10	587 / 5.09	644 / 6.12	696 / 7.18	744 / 8.25	788 / 9.32	829 / 10.38	867 / 11.43	902 / 12.48	935 / 13.52
11000	286 / 1.61	395 / 2.78	473 / 3.79	538 / 4.79	598 / 5.85	654 / 6.95	706 / 8.09	754 / 9.26	799 / 10.43	840 / 11.60	879 / 12.77	916 / 13.94	950 / 15.10
12000	312 / 2.09	414 / 3.39	490 / 4.50	554 / 5.59	612 / 6.71	665 / 7.88	716 / 9.09	764 / 10.33	808 / 11.60	850 / 12.87	890 / 14.15	928 / 15.43	963 / 16.71
13000	338 / 2.66	434 / 4.08	509 / 5.32	571 / 6.49	626 / 7.68	678 / 8.91	727 / 10.19	774 / 11.50	818 / 12.85	860 / 14.21	900 / 15.59	938 / 16.97	974 / 18.36
14000	364 / 3.32	454 / 4.85	528 / 6.23	588 / 7.50	642 / 8.77	692 / 10.06	740 / 11.40	785 / 12.78	828 / 14.19	870 / 15.64	909 / 17.10	947 / 18.58	
15000	389 / 4.09	474 / 5.72	547 / 7.25	606 / 8.63	659 / 9.98	707 / 11.34	753 / 12.74	797 / 14.18	840 / 15.66	880 / 17.18	919 / 18.72		
16000	415 / 4.96	494 / 6.70	567 / 8.38	625 / 9.88	676 / 11.32	723 / 12.75	768 / 14.23	811 / 15.73	852 / 17.27	892 / 18.85			
17000	441 / 5.95	515 / 7.78	586 / 9.62	644 / 11.24	694 / 12.79	740 / 14.31	784 / 15.86	825 / 17.43	865 / 19.03				
18000	467 / 7.06	536 / 8.98	606 / 10.98	663 / 12.74	713 / 14.39	758 / 16.01	800 / 17.63	841 / 19.27					
19000	493 / 8.30	557 / 10.30	626 / 12.45	682 / 14.36	731 / 16.14	776 / 17.86	818 / 19.56						
20000	519 / 9.69	579 / 11.76	646 / 14.06	702 / 16.12	751 / 18.03	794 / 19.85							
21000	545 / 11.21	602 / 13.36	666 / 15.80	722 / 18.02									

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.

Max listed CFM for Recirculating Direct Fired Heaters : A5 = 18000