



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	UNIT DIMENSIONS										HANGING BOX OPENING										SIDE DISCHARGE OPENING										DOWN DISCHARGE OPENING										GAS CONNECTION FORMANCES															
	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF	AG	AH	AI	AJ	AK	AL	AM	AN		AO	AP	AQ	AR	AS	AT									
1-1BT-200-010	164	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	143	1	1	1	1	1	1	1	1	1	1

UNIT INFORMATION

MODEL	BTU RANGE, COEFFICIENT			TURBIDITY RATIO	CONSTRUCTION		GAS PRESSURE RANGE		TWT WEIGHT	CEILING EVAPORATIVE COOLING UNIT		WATER INLET		DRAIN OPENING		OPTIONAL HANGING BOX FILTERS	
	BTU LOW	BTU HIGH	EFFICIENCY		MIN.	MAX.	MIN.	MAX.		MIN. SIZE & QTY	MAX. FLOW RATE	AA	AB	AC	AD	MIN. SIZE & QTY	MIN. SIZE & QTY
1-1BT-200-010	150	150	80%	6	7	14	14	1037	50	4-1/2	6-1/4	18	18	18x24x6 (6)	18x24x6 (6)		

* ADDITIONAL RAIL/GAS CONNECTION ONLY FOR UNITS WITH 3 OR 4 FURNACES

*** COMBUSTION EFFICIENCY OF EVERY UNIT IS 80% OVER THE ENTIRE GAS FIRING RANGE.

*** GAS PRESSURES IN TABLE ARE FOR NATURAL GAS, LP MINIMUM GAS INLET PRESSURE = 11" W.C.

MAX. EVAP WATER PRESSURE = 50 PSI @ 70 DEG. F

