

**R1-IBT-150-G10**

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1200	409 / 0.09	601 / 0.16	758 / 0.25	904 / 0.36	1039 / 0.47	1159 / 0.58	1267 / 0.70	1362 / 0.82	1449 / 0.95
1400	477 / 0.14	648 / 0.22	790 / 0.32	920 / 0.44	1045 / 0.56	1162 / 0.69	1272 / 0.82	1371 / 0.95	1463 / 1.08
1600	545 / 0.21	697 / 0.30	829 / 0.41	947 / 0.53	1060 / 0.67	1170 / 0.81	1275 / 0.96	1375 / 1.10	1468 / 1.25
1800	613 / 0.30	750 / 0.41	873 / 0.51	983 / 0.64	1087 / 0.79	1187 / 0.94	1285 / 1.10	1379 / 1.26	1471 / 1.43
2000	681 / 0.41	804 / 0.53	921 / 0.65	1024 / 0.78	1120 / 0.93	1213 / 1.09	1304 / 1.26	1392 / 1.43	1478 / 1.61
2200	749 / 0.54	860 / 0.68	970 / 0.81	1068 / 0.94	1159 / 1.09	1246 / 1.26	1330 / 1.44	1412 / 1.62	1494 / 1.82
2400	817 / 0.70	918 / 0.86	1022 / 0.99	1116 / 1.13	1202 / 1.29	1284 / 1.46	1363 / 1.64	1441 / 1.84	
2600	885 / 0.89	978 / 1.06	1074 / 1.21	1165 / 1.36	1248 / 1.52	1326 / 1.70	1401 / 1.88		
2800	953 / 1.11	1038 / 1.30	1129 / 1.46	1215 / 1.62	1295 / 1.79	1371 / 1.97			
3000	1021 / 1.37	1100 / 1.57	1185 / 1.75	1267 / 1.92					
3200	1089 / 1.66	1162 / 1.88							

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.