

**R1-IBT-150-G10**

CFM	Static Pressure in Inches W.G.				
	0.000	0.250	0.500	0.750	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	943 / 0.13	1112 / 0.21	1297 / 0.33	1502 / 0.51	1706 / 0.74
1200	1131 / 0.22	1273 / 0.31	1418 / 0.43	1577 / 0.59	1744 / 0.79
1400	1318 / 0.34	1440 / 0.45	1562 / 0.57	1687 / 0.72	1828 / 0.91
1600	1505 / 0.51	1615 / 0.63	1720 / 0.76	1829 / 0.91	
1800	1695 / 0.73	1791 / 0.86			
2000	1883 / 1.00				

**Max Sizeable RPM = 1884 RPM. Table shown extended beyond this point for reference only.**

Motor BMN48-750I2-50-230/277 has an rpm range of 800 to 1800.

Motor BMN48-750I2-60-230/277 has an rpm range of 800 to 1800.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 800 to 1800.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 800 to 1800.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 800 to 1800.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 800 to 1800.