

R1-IBT-300-150-150-G10

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1600	609 / 0.24	743 / 0.34	868 / 0.44	994 / 0.59	1116 / 0.78	1227 / 0.99	1330 / 1.20	1423 / 1.41	1509 / 1.61
1800	685 / 0.34	806 / 0.45	917 / 0.56	1029 / 0.70	1141 / 0.89	1248 / 1.10	1349 / 1.33	1443 / 1.57	1531 / 1.81
2000	761 / 0.47	872 / 0.60	972 / 0.71	1072 / 0.85	1174 / 1.02	1274 / 1.23	1371 / 1.47	1463 / 1.72	1550 / 1.98
2200	837 / 0.62	940 / 0.77	1031 / 0.89	1122 / 1.02	1213 / 1.19	1306 / 1.39	1397 / 1.62	1485 / 1.88	
2400	913 / 0.81	1009 / 0.98	1093 / 1.11	1176 / 1.24	1260 / 1.40	1345 / 1.60	1429 / 1.82		
2600	989 / 1.03	1079 / 1.22	1158 / 1.36	1235 / 1.50	1311 / 1.66	1389 / 1.84			
2800	1065 / 1.28	1150 / 1.49	1224 / 1.65	1295 / 1.80	1367 / 1.96				
3000	1141 / 1.58	1221 / 1.81	1291 / 1.98						

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.