

R1-IBT-300-150-150-G10

CFM	Static Pressure in Inches W.G.				
	0.000	0.250	0.500	0.750	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	1048 / 0.17	1215 / 0.27	1383 / 0.40	1555 / 0.56	1727 / 0.77
1200	1257 / 0.30	1395 / 0.41	1536 / 0.54	1678 / 0.71	1821 / 0.90
1400	1466 / 0.47	1586 / 0.60	1705 / 0.74	1825 / 0.91	
1600	1675 / 0.70	1780 / 0.84			

Max Sizeable RPM = 1884 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-750I2-50-230/277 has an rpm range of 900 to 1800.

Motor BMN48-750I2-60-230/277 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 900 to 1800.