

R2-IBT-400-200-200-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	504 / 0.34	612 / 0.49	729 / 0.73	810 / 0.92	873 / 1.07	926 / 1.20	974 / 1.32	1018 / 1.43	1060 / 1.53
2250	567 / 0.48	658 / 0.64	771 / 0.90	857 / 1.14	923 / 1.34	978 / 1.51	1027 / 1.66	1071 / 1.80	1112 / 1.93
2500	630 / 0.66	708 / 0.82	811 / 1.09	901 / 1.38	971 / 1.64	1029 / 1.85	1079 / 2.04	1124 / 2.22	1166 / 2.38
2750	693 / 0.88	761 / 1.05	852 / 1.31	943 / 1.64	1017 / 1.95	1078 / 2.22	1129 / 2.45	1176 / 2.67	1218 / 2.86
3000	756 / 1.14	817 / 1.32	897 / 1.58	984 / 1.93	1060 / 2.28	1124 / 2.61	1178 / 2.89	1226 / 3.15	1269 / 3.39
3250	819 / 1.46	874 / 1.64	944 / 1.89	1024 / 2.25	1101 / 2.64	1167 / 3.01	1224 / 3.35	1274 / 3.67	1319 / 3.95
3500	882 / 1.82	932 / 2.01	994 / 2.26	1067 / 2.61	1142 / 3.02	1209 / 3.45	1269 / 3.84	1321 / 4.21	1367 / 4.54
3750	945 / 2.24	991 / 2.44	1046 / 2.69	1112 / 3.03	1182 / 3.45	1250 / 3.91	1311 / 4.35	1365 / 4.77	
4000	1008 / 2.71	1050 / 2.93	1101 / 3.19	1160 / 3.52	1225 / 3.93	1290 / 4.41	1352 / 4.89		
4250	1071 / 3.25	1111 / 3.48	1156 / 3.74	1210 / 4.07	1269 / 4.48	1331 / 4.96			
4500	1134 / 3.86	1171 / 4.10	1214 / 4.37	1262 / 4.70					
4750	1197 / 4.54	1232 / 4.79							

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.