

R2-IBT-400-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2500	386 / 0.29	471 / 0.38	584 / 0.54	680 / 0.75	766 / 0.98	845 / 1.22	919 / 1.46	989 / 1.70	1054 / 1.94
3000	463 / 0.50	526 / 0.59	620 / 0.75	711 / 0.96	792 / 1.21	866 / 1.48	935 / 1.76	1001 / 2.05	1064 / 2.34
3500	540 / 0.80	589 / 0.90	663 / 1.04	746 / 1.25	823 / 1.51	894 / 1.79	960 / 2.10	1022 / 2.41	1082 / 2.74
4000	617 / 1.19	658 / 1.30	715 / 1.44	786 / 1.63	858 / 1.89	926 / 2.18	989 / 2.50	1049 / 2.84	1106 / 3.19
4500	694 / 1.69	729 / 1.81	775 / 1.96	833 / 2.14	897 / 2.38	961 / 2.67	1022 / 2.99	1080 / 3.34	1135 / 3.71
5000	771 / 2.32	802 / 2.45	840 / 2.61	887 / 2.79	942 / 3.01	1000 / 3.28	1058 / 3.60	1112 / 3.93	1167 / 4.33
5500	849 / 3.08	876 / 3.23	908 / 3.40	947 / 3.58	994 / 3.79	1045 / 4.05	1098 / 4.35	1151 / 4.69	
6000	926 / 4.00	950 / 4.17	979 / 4.34	1012 / 4.53	1051 / 4.74	1095 / 4.99			

Max Sizeable RPM = 1400 RPM. Table shown extended beyond this point for reference only.