

R2-IBT-600-300-300-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2500	432 / 0.32	537 / 0.49	629 / 0.65	712 / 0.83	795 / 1.03	877 / 1.26	953 / 1.51	1020 / 1.76	1079 / 2.02
3000	518 / 0.55	605 / 0.75	690 / 0.95	763 / 1.14	832 / 1.36	901 / 1.59	970 / 1.85	1038 / 2.12	1104 / 2.41
3500	604 / 0.88	676 / 1.11	755 / 1.34	823 / 1.57	885 / 1.80	944 / 2.04	1003 / 2.30	1063 / 2.58	1122 / 2.88
4000	690 / 1.31	751 / 1.57	822 / 1.84	887 / 2.10	945 / 2.36	1000 / 2.62	1052 / 2.89	1104 / 3.18	1155 / 3.48
4500	777 / 1.87	828 / 2.15	892 / 2.46	953 / 2.76	1009 / 3.05	1061 / 3.34	1109 / 3.63	1156 / 3.93	1202 / 4.25
5000	863 / 2.57	908 / 2.88	963 / 3.21	1021 / 3.55	1075 / 3.88	1124 / 4.20	1171 / 4.52	1215 / 4.85	
5500	949 / 3.42	989 / 3.75	1038 / 4.12	1090 / 4.49	1142 / 4.86				
6000	1036 / 4.44	1071 / 4.80							

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.