

R3-IBT-1000-300-300-400-G18

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
5500	482 / 1.27	553 / 1.35	607 / 1.59	663 / 1.92	722 / 2.33	785 / 2.79	848 / 3.29	910 / 3.81	968 / 4.33
6000	526 / 1.65	594 / 1.72	644 / 1.95	694 / 2.28	746 / 2.67	801 / 3.14	859 / 3.65	917 / 4.20	974 / 4.76
6500	569 / 2.10	635 / 2.15	682 / 2.38	727 / 2.70	774 / 3.09	824 / 3.55	875 / 4.06	928 / 4.62	982 / 5.21
7000	613 / 2.63	676 / 2.65	721 / 2.88	763 / 3.20	806 / 3.58	850 / 4.03	897 / 4.54	945 / 5.10	994 / 5.70
7500	656 / 3.23	717 / 3.24	760 / 3.46	800 / 3.77	840 / 4.15	880 / 4.59	922 / 5.09	965 / 5.65	1011 / 6.25
8000	700 / 3.92	759 / 3.91	800 / 4.12	838 / 4.43	875 / 4.80	912 / 5.24	951 / 5.73	990 / 6.28	1031 / 6.87
8500	744 / 4.70	801 / 4.67	841 / 4.87	877 / 5.18	912 / 5.55	947 / 5.98	982 / 6.47	1019 / 7.00	

Max Sizeable RPM = 1200 RPM. Table shown extended beyond this point for reference only.