

**R4-IBT-1000-300-300-400-920**

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
6000	363 / 0.93	413 / 1.13	478 / 1.47	545 / 1.88	609 / 2.31	667 / 2.74	721 / 3.17	770 / 3.61	815 / 4.04
7000	424 / 1.47	464 / 1.69	516 / 2.02	573 / 2.46	631 / 2.94	686 / 3.44	739 / 3.95	788 / 4.45	834 / 4.96
8000	484 / 2.20	518 / 2.43	561 / 2.76	609 / 3.20	659 / 3.71	710 / 4.26	759 / 4.83	806 / 5.41	851 / 5.98
9000	545 / 3.13	574 / 3.37	610 / 3.71	650 / 4.15	694 / 4.67	739 / 5.25	784 / 5.86	828 / 6.50	871 / 7.14
10000	606 / 4.29	632 / 4.56	662 / 4.90	696 / 5.33	734 / 5.85	774 / 6.44	814 / 7.08	855 / 7.76	895 / 8.46
11000	666 / 5.71	689 / 6.00	716 / 6.35	746 / 6.78	778 / 7.30	813 / 7.88	849 / 8.54	886 / 9.24	923 / 9.97
12000	727 / 7.42	748 / 7.72	771 / 8.09	797 / 8.52	826 / 9.03	856 / 9.62	888 / 10.27	922 / 10.98	955 / 11.73
13000	787 / 9.43	806 / 9.75	828 / 10.13	851 / 10.58	876 / 11.09	903 / 11.67	931 / 12.32	961 / 13.03	992 / 13.79

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.