

R4-IBT-1400-300-300-400-400-920

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
8000	494 / 2.27	539 / 2.59	588 / 3.00	646 / 3.53	700 / 4.07	743 / 4.57	777 / 5.04	807 / 5.48	834 / 5.90
9000	555 / 3.23	596 / 3.58	637 / 4.01	685 / 4.53	738 / 5.15	785 / 5.76	824 / 6.33	857 / 6.87	886 / 7.37
10000	617 / 4.42	654 / 4.82	690 / 5.26	730 / 5.79	775 / 6.41	822 / 7.10	865 / 7.79	902 / 8.43	934 / 9.04
11000	679 / 5.89	713 / 6.31	745 / 6.78	779 / 7.32	818 / 7.94	860 / 8.66	903 / 9.42	942 / 10.17	977 / 10.90
12000	740 / 7.65	772 / 8.11	801 / 8.61	832 / 9.15	865 / 9.78	901 / 10.49	940 / 11.28	979 / 12.11	
13000	802 / 9.72	831 / 10.22	859 / 10.75	886 / 11.32	915 / 11.95	947 / 12.66	981 / 13.44		

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.