

R4-IBT-400-920

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
8000	398 / 1.49	455 / 1.73	506 / 2.16	555 / 2.64	601 / 3.13	647 / 3.62	693 / 4.13	738 / 4.64	782 / 5.17
9000	447 / 2.12	500 / 2.36	546 / 2.81	590 / 3.33	632 / 3.87	674 / 4.42	715 / 4.97	756 / 5.54	796 / 6.11
10000	497 / 2.91	545 / 3.14	588 / 3.61	628 / 4.16	667 / 4.74	705 / 5.34	742 / 5.95	779 / 6.57	816 / 7.19
11000	546 / 3.87	590 / 4.09	630 / 4.57	668 / 5.14	704 / 5.77	739 / 6.42	774 / 7.08	808 / 7.75	841 / 8.42
12000	596 / 5.02	637 / 5.24	674 / 5.71	709 / 6.31	743 / 6.96	776 / 7.66	808 / 8.37	840 / 9.09	870 / 9.80
13000	646 / 6.38	684 / 6.59	719 / 7.06	752 / 7.67	784 / 8.35	814 / 9.08	845 / 9.84	874 / 10.61	903 / 11.39

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.