

**R4-IBT-800-400-400-920**

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
7000	376 / 1.19	438 / 1.52	493 / 1.85	548 / 2.24	603 / 2.68	656 / 3.15	706 / 3.66	754 / 4.17	800 / 4.69	842 / 5.21	883 / 5.74	921 / 6.26	958 / 6.79
8000	429 / 1.78	486 / 2.17	534 / 2.53	582 / 2.93	630 / 3.38	678 / 3.88	725 / 4.41	771 / 4.98	814 / 5.55	856 / 6.14	896 / 6.73	935 / 7.33	971 / 7.93
9000	483 / 2.53	535 / 2.98	578 / 3.38	621 / 3.80	663 / 4.26	706 / 4.78	749 / 5.33	791 / 5.92	832 / 6.54	873 / 7.17	911 / 7.82	949 / 8.48	985 / 9.15
10000	537 / 3.47	584 / 3.98	625 / 4.42	663 / 4.88	701 / 5.36	740 / 5.88	778 / 6.45	816 / 7.05	855 / 7.69	892 / 8.36	929 / 9.05	966 / 9.76	
11000	590 / 4.62	635 / 5.19	672 / 5.68	707 / 6.17	742 / 6.68	777 / 7.22	812 / 7.80	847 / 8.42	882 / 9.07	917 / 9.76	951 / 10.47	985 / 11.21	
12000	644 / 6.00	685 / 6.63	720 / 7.18	753 / 7.70	786 / 8.25	817 / 8.81	849 / 9.41	881 / 10.04	913 / 10.70	945 / 11.40	977 / 12.13		
13000	697 / 7.63	736 / 8.32	770 / 8.92	800 / 9.50	830 / 10.07	860 / 10.67	889 / 11.29	919 / 11.93	948 / 12.61	978 / 13.32			

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.