



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	WEIGHT	UNIT DIMENSIONS												DISCHARGE OPENING		TONNAGE RANGE	
		A	B	C	D	E	G	H	J	N	P	R	S	MIN	MAX		
G10	605 LBS	74-3/8	39-3/8	42-3/4	39	3-3/4	21	44-3/8	65-13/16	13-1/4	11-1/2	3-7/8	1-3/4	3	Ton	12.5	Ton
G12	845 LBS	82-3/8	49-3/8	47-3/4	44	3-3/4	31	53-5/8	74-5/8	15-3/4	13-9/16	7-5/8	1-15/16	5	Ton	20	Ton
G15	855 LBS	82-3/8	49-3/8	47-3/4	44	3-3/4	31	53-5/8	74-5/8	18-3/4	16	6-1/8	5-1/2	5	Ton	20	Ton
G18	1030 LBS	87-3/8	54-3/8	56-3/8	51-1/8	5-1/4	35	51-5/8	79-3/16	22	19	6-1/2	7	10	Ton	25	Ton
920	1725 LBS	118-1/2	60-7/16	64-3/8	59-1/8	5-1/4	42	76-3/8	104-9/32	24-7/8	24-7/8	8-9/16	1-1/8	20	Ton	40	Ton
925	2235 LBS	128-1/2	79-7/16	68-7/16	63-3/16	5-1/4	52-3/4	71-3/8	114-21/32	31-3/8	31-3/8	10-11/16	13-13/16	30	Ton	50	Ton

UNIT INFORMATION

MODEL	FILTER SIZE & QTY	MAX. FILTER VELOCITY
G10	16"x20"x2" (3)	@3500 CFM = 667 FPM
G12	20"x25"x2" (3)	@5000 CFM = 580 FPM
G15	20"x25"x2" (3)	@6000 CFM = 696 FPM
G18	16"x20"x2" (6)	@8000 CFM = 762 FPM
920	16"x20"x2" (10)	@15000 CFM = 857 FPM
925	20"x25"x2" (8)	@22000 CFM = 957 FPM