



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	WEIGHT	UNIT DIMENSIONS										DISCHARGE OPENING				TONNAGE RANGE	
		A	B	C	D	E	F	G	H	J	N	P	R	S	MIN.	MAX.	
G10	605 LBS	74-3/8	39-3/8	42-3/4	39	3-3/4	21	44-3/8	71	13-1/4	11-1/2	6-3/8	11-7/8	3	12.5	20	
G12	845 LBS	82-3/8	49-3/8	47-3/4	44	3-3/4	31	53-5/8	79	15-3/4	13-9/16	10-1/8	13-1/16	5	20	20	
G15	855 LBS	82-3/8	49-3/8	47-3/4	44	3-3/4	31	53-5/8	79	18-3/4	16	8-5/8	14-1/16	5	20	20	
G18	1030 LBS	87-3/8	54-3/8	56-3/8	51-1/8	5-1/4	35	51-5/8	84	22	19	9	17-7/8	10	25	25	
920	1725 LBS	118-1/2	60-7/16	64-3/8	59-1/8	5-1/4	42	76-3/8	115-3/16	24-7/8	24-7/8	11-1/16	19-1/8	20	40	40	
925	2235 LBS	128-1/2	79-7/16	68-7/16	63-3/16	5-1/4	42	76-3/8	125-3/16	31-3/8	31-3/8	13-3/16	21-9/16	30	50	50	

UNIT INFORMATION

MODEL FILTER SIZE & QTY MAX. FILTER VELOCITY

G10	16"x20"x2" (3)	@3500 CFM = 667 FPM
G12	20"x25"x2" (3)	@5000 CFM = 580 FPM
G15	20"x25"x2" (3)	@6000 CFM = 696 FPM
G18	16"x20"x2" (6)	@8000 CFM = 762 FPM
920	16"x20"x2" (10)	@15000 CFM = 857 FPM
925	20"x25"x2" (8)	@22000 CFM = 957 FPM