



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	WEIGHT	A	B	C	D	E	F	J	K	L	M	N	P	R	S	U	V		
G10	460 LBS	106-5/8	27-3/8	29-3/4	26-1/16	3-3/4	36	31-1/8	73-1/4	3-1/8	16	3-4/16	21-7/8	5-3/4	6	3/8	11-1/2	13-1/4	11-7/8
G12	705 LBS	114-5/8	37-3/8	36-3/4	33-1/16	3-3/4	48	39-1/8	81-1/4	5-1/8	24	3-4/16	28-7/8	5-3/4	15	3/4	13-9/16	10-1/8	13-1/16
G15	715 LBS	114-5/8	37-3/8	36-3/4	33-1/16	3-3/4	48	39-1/8	81-1/4	5-1/8	24	3-4/16	28-7/8	5-3/4	15	3/4	13-9/16	10-1/8	13-1/16
G18	860 LBS	125-7/8	41-3/8	43-3/8	38-1/16	5-1/4	60	44-1/8	86-1/4	4-5/8	29-1/4	3-7/8	7-1/2	9	19	22	17-7/8	17-7/8	17-7/8
920	1405 LBS	153-7/8	48-1/16	51-3/8	46-1/8	5-1/4	60	63-3/16	117-3/8	4-5/8	36	1-1/4	7-1/2	11-1/16	24	7/8	24-7/8	19-1/8	19-1/8
925	1925 LBS	163-7/8	59-3/16	58-3/8	53-1/8	5-1/4	72	73-3/16	127-3/8	4-7/8	7-1/2	13-3/16	31-3/8	16	31-3/8	21-9/16	21-9/16	21-9/16	21-9/16

HOT WATER COIL MODULE

MODEL	WEIGHT	TOTAL CAPACITY (MBH)	PIPE CONNECTION
G10	460 LBS	165.63	2"
G12	705 LBS	320.88	2"
G15	715 LBS	320.88	2"
G18	860 LBS	514.97	1-1/2"
920	1405 LBS	831.87	2-1/2"
925	1925 LBS	1230.16	3"

STEAM COIL MODULE

MODEL	WEIGHT	TOTAL CAPACITY (MBH)	PIPE CONNECTION	PSI	G	GG	H	HH
G10	460 LBS	176.49	2-1/2"	5	8-3/4"	53-5/16"	16-15/16"	53-5/16"
G12	705 LBS	328.19	2-1/2"	5	8-3/4"	53-5/16"	18-3/8"	53-5/16"
G15	715 LBS	328.19	2-1/2"	5	8-3/4"	53-5/16"	18-3/8"	53-5/16"
G18	855 LBS	505.64	2-1/2"	5	10-1/4"	59-5/16"	23-5/8"	59-5/16"
920	1380 LBS	812.24	2-1/2"	5	10-1/4"	62-15/32"	28-5/8"	62-15/32"
925	1920 LBS	1234.45	2-1/2"	5	10-1/4"	62-15/32"	31-3/4"	62-15/32"

V-BANK FILTER

MODEL	FILTER SIZE & QTY	MAX. FILTER VELOCITY
G10	20"x25"x2" (3)	@3500 CFM = 406 FPM
G12	16"x20"x2" (8)	@5000 CFM = 358 FPM
G15	16"x20"x2" (8)	@6000 CFM = 429 FPM
G18	20"x25"x2" (8)	@8000 CFM = 348 FPM
920	16"x20"x2" (15)	@15000 CFM = 572 FPM
925	20"x25"x2" (12)	@22000 CFM = 638 FPM