

SA10RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500	371 / 0.11	548 / 0.19	703 / 0.29	837 / 0.39	956 / 0.49	1064 / 0.60	1162 / 0.72	1253 / 0.84	1338 / 0.96
2000	494 / 0.25	628 / 0.36	759 / 0.48	876 / 0.61	984 / 0.74	1085 / 0.87	1178 / 1.01	1265 / 1.15	1349 / 1.30
2500	618 / 0.49	723 / 0.63	833 / 0.78	936 / 0.93	1033 / 1.08	1124 / 1.24	1209 / 1.40	1291 / 1.56	1370 / 1.73
3000	741 / 0.85	827 / 1.01	919 / 1.18	1009 / 1.36	1096 / 1.54	1179 / 1.73	1258 / 1.92		
3500	865 / 1.36	937 / 1.53	1015 / 1.73	1094 / 1.93					

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.