

SA10RA

CFM	Static Pressure in Inches W.G.							
	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000	309 / 0.02	442 / 0.07	573 / 0.15	693 / 0.27	799 / 0.41	892 / 0.57	975 / 0.74	1050 / 0.92
1500	462 / 0.08	552 / 0.13	641 / 0.21	730 / 0.31	817 / 0.43	902 / 0.58	982 / 0.76	1059 / 0.95
2000	616 / 0.19	685 / 0.26	752 / 0.34	818 / 0.44	884 / 0.55	951 / 0.68	1017 / 0.84	
2500	769 / 0.36	825 / 0.45	880 / 0.54	933 / 0.65	986 / 0.76	1039 / 0.89		
3000	923 / 0.63	970 / 0.73	1016 / 0.84	1061 / 0.95				

Max Sizeable RPM = 1075 RPM. Table shown extended beyond this point for reference only.

Motor BMN48-750I2-50-230/277 has an rpm range of 300 to 1075.

Motor BMN48-750I2-60-230/277 has an rpm range of 300 to 1075.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 300 to 1075.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 300 to 1075.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 300 to 1075.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 300 to 1075.