

SA12RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	328 / 0.14	458 / 0.22	601 / 0.32	723 / 0.44	830 / 0.56	927 / 0.69	1015 / 0.82	1092 / 0.94	1174 / 1.09
2500	410 / 0.27	503 / 0.37	626 / 0.49	739 / 0.62	839 / 0.76	931 / 0.91	1017 / 1.06	1097 / 1.22	1172 / 1.37
3000	492 / 0.47	563 / 0.59	661 / 0.72	763 / 0.86	858 / 1.02	945 / 1.18	1026 / 1.35	1103 / 1.53	1176 / 1.71
3500	574 / 0.75	631 / 0.88	708 / 1.03	796 / 1.18	883 / 1.35	966 / 1.53	1043 / 1.72	1116 / 1.91	1186 / 2.11
4000	656 / 1.12	704 / 1.27	765 / 1.43	838 / 1.60	916 / 1.78	992 / 1.97	1066 / 2.17	1136 / 2.39	1203 / 2.60
4500	738 / 1.60	779 / 1.77	830 / 1.94	890 / 2.13	957 / 2.32	1026 / 2.52	1094 / 2.74	1161 / 2.96	
5000	820 / 2.19	856 / 2.38	899 / 2.57	950 / 2.77	1007 / 2.98				

Max Sizeable RPM = 1300 RPM. Table shown extended beyond this point for reference only.